



Fig.ZRF0

**压力 Pressure: CLASS150**

- ◆ 栓接阀盖
- ◆ 弹性闸板
- ◆ 10"以上采用分体式支架
- ◆ Bolted bonnet
- ◆ Flexible wedge gate
- ◆ 10" and above: two pieces yoke

**主要外形尺寸和重量 Main dimensions & Weight**

CALSS 150

规格 Size		尺寸 Dimensions					重量 weight (Kg)		扭矩 (N.m)	Cv值
mm	in.	L (RF)	L (BM)	L (RM)	H	W	RF	BM	Torque	
40	1-1/2	165	165	178	386	250	24	21	12	-
50	2	178	216	190	391	250	27	23	13	-
65	2-1/2	190	241	203	408	250	37	33	13	-
80	3	203	283	216	457	250	40	35	15	710
100	4	229	305	241	538	250	52	47	27	1300
150	6	267	403	279	693	380	90	84	36	3100
200	8	292	419	305	863	380	145	137	63	5720
250	10	330	457	343	1036	450	225	207	84	8940
300	12	356	502	368	1130	450	310	253	131	13350
350	14	381	572	394	1272	610	445	376	151	16275
400	16	406	610	419	1447	610	540	440	235	21560
450	18	432	660	445	1701	720	800	722	285	28720
500	20	457	711	470	1795	720	900	863	341	35760
600	24	508	813	521	2189	720	1600	1519	602	52165
650	26	559	864	-	2387	860	1850	1755	-	63500
700	28	610	914	-	2590	860	2100	1995	-	74800
750	30	610	914	622	2819	860	2700	2404	1079	86235
800	32	711	965	-	2870	860	3100	2840	-	103000
900	36	711	1016	724	2997	860	3950	3690	1497	129500
1000	40	813	1067	-	3302	1020	4650	-	-	175860
1050	42	813	1143	-	3479	1020	5100	-	-	223300
1200	48	1067	1371	-	3962	1020	6500	-	-	335500