


**主要外形尺寸 PN1.6MPa CLASS 150**

mm

DN	mm	10	20	25	40	50	65	80	100	125	150	200
DN	in	1/2	3/4	1	1 1/2	2	2 1/2	3	4	5	6	8
L	RF	108	117	127	166	176	190	203	208	260	264	317
L <sub>1</sub>	RF	140	152	165	190	218	241	263	265	324	327	381
	M	58	63	75	95	107	140	152	176	202	212	247
	M <sub>1</sub>	130	138	150	180	208	240	268	268	330	338	390
	H	7	7	7	7	7	7	7	7	7	7	7
H <sub>1</sub>	H <sub>1</sub>	7	7	7	7	7	7	7	7	7	7	7
	H <sub>2</sub>	7	7	7	7	7	7	7	7	7	7	7
	H <sub>3</sub>	7	7	7	7	7	7	7	7	7	7	7
	H <sub>4</sub>	7	7	7	7	7	7	7	7	7	7	7
H <sub>5</sub>	A	200	204	207	264	266	270	281	281	348	348	381
	A <sub>1</sub>	150	158	162	190	208	220	228	227	287	287	327
	A <sub>2</sub>	130	138	147	180	180	190	190	202	250	250	285
	A <sub>3</sub>	130	138	148	181	187	187	187	187	238	238	280
H <sub>6</sub>	D	7	7	7	7	67	66	67	66	66	70	70
	D <sub>1</sub>	7	7	7	7	67	66	66	66	66	66	66
	D <sub>2</sub>	7	7	7	7	100	100	100	100	100	100	100
重量 kg (lb)	平球	2.5	3	3	7	10	15	18	30	38	48	100
	气驱	6	11.7	16.5	42.8	45.0	58.5	70	107.7	133.7	160.5	290
	电驱	7	7	7	7	37	35.4	44	55	70	108	170