


 Figure No.  
 W50F005, 400T  
 W50F005, 400T

 W50F005, 400T  
 W50F005, 400T

 A500F005, 400T  
 A500F005, 400T

 W50F005, 400T  
 W50F005, 400T

## 主要外形尺寸 PN2.5, 4.0MPa CLASS 200

mm

DN	mm	15	20	25	40	50	65	80	100	125	150	200
PN2.5	in	3/8	3/4	1	1 1/2	2	2 1/2	3	4	5	6	8
L	mm	140	150	160	180	210	240	260	300	340	400	500
手 动	DN	140	150	160	180	210	240	260	300	340	400	500
	M	50	60	75	90	100	140	150	175	200	270	340
	M0	130	130	160	200	230	260	260	300	330	400	500
蜗 轮 操 作	DN	∕	∕	∕	∕	∕	∕	∕	∕	∕	200	300
	DN	∕	∕	∕	∕	∕	∕	∕	∕	∕	400	500
	DN	∕	∕	∕	∕	∕	∕	∕	∕	∕	380	520
气 动 操 作	A	200	200	267	260	340	370	450	560	640	740	900
	A1	100	100	130	130	170	180	220	270	320	370	450
	A2	370	380	347	400	430	430	500	520	610	610	660
电 动 操 作	AA	130	130	160	180	210	210	240	260	300	370	500
	B	∕	∕	∕	∕	410	480	570	700	800	770	770
	B1	∕	∕	∕	∕	310	380	480	600	700	680	680
直 接 操 作	DN	∕	∕	∕	∕	180	180	180	180	180	180	180
	手 动	3	4	5	11	15	24	30	55	64	118	150
	气 动	10	15.7	19.5	40.8	43.8	54.9	68	104	127.5	204.5	267
电 动	∕	∕	∕	∕	39	37	43	77	130	143	208	

注: 直接操作尺寸, 请参照尺寸规格表A、B。