



## 主要尺寸 (Main Dimensions)

## PN1.6MPa CLASS 150

尺寸	公称				口径				法兰连接尺寸				气动				电动				重量	
	DN	mm	英寸	mm	DN	mm	英寸	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	磅
50	2	150	250	150	40	102	120	2	2	2	2	207	170	80	150	1	2	2	2	12	27	11
65	2 1/2	175	281	175	50	125	140	2	2	2	2	230	190	100	160	1	2	2	2	16	35.2	15.2
80	3	200	330	200	60	150	160	2	2	2	2	250	210	110	180	1	2	2	2	20	44.5	20.2
100	4	225	365	225	80	175	190	2	2	2	2	287	230	120	200	1	2	2	2	25	55	24
125	5	250	411	250	100	200	210	2	2	2	2	320	260	130	230	1	2	2	2	30	66.4	29.4
150	6	275	457	275	120	225	240	2	2	2	2	350	290	140	250	1	2	2	2	35	77	34
200	8	325	531	325	160	275	290	2	2	2	2	421	340	160	300	1	2	2	2	45	99.5	44.7
250	10	375	605	375	200	325	340	2	2	2	2	480	390	180	350	1	2	2	2	55	121.5	55
300	12	425	679	425	240	375	390	2	2	2	2	540	440	200	400	1	2	2	2	65	143.5	65
350	14	475	753	475	280	425	440	2	2	2	2	600	490	220	450	1	2	2	2	75	165.5	75
400	16	525	827	525	320	475	490	2	2	2	2	660	540	240	500	1	2	2	2	85	187.5	85
450	18	575	901	575	360	525	540	2	2	2	2	720	590	260	550	1	2	2	2	95	209.5	95
500	20	625	975	625	400	575	590	2	2	2	2	780	640	280	600	1	2	2	2	105	231.5	105
600	24	700	1116	700	480	650	670	2	2	2	2	870	720	320	680	1	2	2	2	125	276.5	125
650	26	750	1190	750	520	700	720	2	2	2	2	930	770	340	730	1	2	2	2	135	298.5	135
700	28	800	1264	800	560	750	780	2	2	2	2	990	820	360	780	1	2	2	2	145	320.5	145
800	32	900	1466	900	640	830	860	2	2	2	2	1080	900	400	860	1	2	2	2	165	365.5	165
900	36	1000	1628	1000	720	910	940	2	2	2	2	1170	980	440	940	1	2	2	2	185	410.5	185
1000	40	1100	1790	1100	800	990	1020	2	2	2	2	1260	1060	480	1020	1	2	2	2	205	455.5	205
1200	48	1250	2042	1250	960	1130	1160	2	2	2	2	1410	1210	560	1160	1	2	2	2	245	540.5	245
1500	60	1500	2494	1500	1200	1370	1400	2	2	2	2	1650	1450	680	1400	1	2	2	2	305	670.5	305
1800	72	1700	2846	1700	1440	1610	1640	2	2	2	2	1890	1690	800	1640	1	2	2	2	365	800.5	365
2000	80	1850	3098	1850	1600	1750	1780	2	2	2	2	2040	1840	880	1780	1	2	2	2	405	890.5	405

注: 详细尺寸尺寸, 请洽设计部门或销售人员。

备注: 表中, 带斜杠表示法兰连接, A/C表示带颈结构, 带斜杠表示结构型式如图中。