

压力 Pressure: CLASS100-1500 PN10.0-42.0

- 锻造铸钢
Pressure-cast forged
- 锻造衬套
Forged sleeve
- 锻制 (法兰)
Forged (flange)
- 法兰连接(焊接型)
Flange ends (Butt-welding-type)



Fig. 1000001


技术规范 Technical Specification

技术规格 Technical Specification	ASME B16.34 (ANSI)	GB6109
设计标准 Design Standard	ASME B16.34 (ANSI)	GB15589 GB7309
设计温度范围 Design Temperature Rating	ASME B16.34	GB7309
密封材料 Face-Face	ASME B16.34	GB15589 GB7309
法兰密封形式 Flange Ends	ASME B16.34	GB15589 GB7309
焊接连接 Butt-welding Ends	ASME B16.34	GB7309
检验与测试 Inspection & Test	API598	GB7309

主要材料尺寸和重量 Main Dimensions & Weight

压力 Pressure	公称尺寸 Nominal Size		进出口口径 Valve Main Dimension					重量 Weight(kg)
	mm	in.	法兰口径 DN	Lmm	Lmm	Lmm	H	
CLASS100 PN10.0	15	1/2	15	210	210	210	117.5	10.0
	20	3/4	18	220	220	220	117.5	11.0
	25	1	20	234	234	234	117.5	12.0
	32	1-1/4	25	270	270	270	140	16.0
	40	1-1/2	30.5	305	305	305	140	18.1
CLASS150 PN15.0	15	1/2	15	210	210	210	117.5	10.0
	20	3/4	18	220	220	220	117.5	11.0
	25	1	20	234	234	234	117.5	12.0
	32	1-1/4	25	270	270	270	140	16.0
	40	1-1/2	30.5	305	305	305	140	18.1
CLASS3000 PN30.0	15	1/2	15	204	204	204	120	12.0
	20	3/4	18	210	210	210	120	14.0
	25	1	20	220	220	220	120	16.0
	32	1-1/4	25	240	240	240	130	18.0
	40	1-1/2	30.5	264	264	264	130	20.0
50	2	40.5	401	401	404.0	130	24.0	