

Pressure: CLASS100-1500 PN10-20.0

- 焊接球閥 / 焊接式球閥
Welded ball valve / welded ball valve
- 全通 Full port
- 彈簧式球閥形式
Spring or Lift type
- 螺紋連接式平端平端面
Threaded ends or B1/ends



Fig.1010/100



Fig.1010/200

Technical Specification

技術規格 Technical Specification	API607/API6D	GB12234
設計標準 Design Standard	BS5592	JB/T1304
壓力溫度等級 Pressure-Temperature Rating	ASME B16.34	GB/T12234
結構形式 Face-to-Face	工廠製造 Factory Standard	JB/T1304
平端平端面 End-to-End Ends	ASME B16.34	JB/T1304
螺紋端 Threaded Ends	ASME B1.20.1	GB/T12234
檢驗與試驗 Inspection & Test	API598	JB/T1304

主要尺寸及重量 Main Dimensions & Weight

壓力 Pressure	球閥形式 Ball Valve Type	單位 Unit		球閥尺寸 Valve Main Dimension						重量 Weight (kg) 磅重
		mm		in.		L		H		
		公稱 Nominal	實際 Actual	公稱 Nominal	實際 Actual	公稱 Nominal	實際 Actual	L	H	
CLASS100 PN10.0	彈簧式 Spring Type	15	40	1.72	2.75	40	48	74	64	1.2
		20	50	2.74	1.72	51	72	80	61	1.4
		25	65	1	2.74	51	78	111	75	2.2
		32	80	1-104	1	64	74	120	84	3.8
		40	100	1-102	1-176	76	76	152	102	5.8
		50	125	2	1-120	120.5	120.5	170	118	8.8
CLASS1500 PN20.0	彈簧式 Spring Type	15	40	1.72	2.75	40	48	74	64	1.2
		20	50	2.74	1.72	51	72	80	61	1.4
		25	65	1	2.74	51	78	111	75	1.8
		32	80	1-104	1	64	74	120	84	2.4
		40	100	1-102	1-176	76	76	152	102	4.6
		50	125	2	1-120	120.5	120.5	170	130	7.2