

压力等级 Pressure PN1.6-10.0/CLASS150-250



Fig.2PW3



Fig.2PW2



Fig.2PW1




Fig.2PW4

主要尺寸和重量 Main dimensions & Weight

PN1.6, 10 CLASS150

口径 Dia mm	in	Lmm	L1mm	P-Hand operated			S-Hand operated			ELECTRO operated			Z	Y	重量 Weight(kg)		重量 Weight (lb)
				M	M1	M2	B	B1	B2	B	B1	B2			GW	GW	
25	1	127	127	275	325	350	-	-	-	-	-	-	85	93	-	-	-
32	1-1/4	140	140	300	350	350	-	-	-	-	-	-	75	105	-	-	-
40	1-1/2	160	160	325	375	380	-	-	-	-	-	-	75	115	-	-	14
50	2	175	175	475	500	500	-	-	-	500	517	500	85	107	45	54	15
65	2-1/2	190	190	525	525	500	-	-	-	747	637	500	85	152	55	75	21
80	3	225	225	600	600	500	-	-	-	812	672	500	100	175	60	73	28
100	4	255	255	700	700	500	-	-	-	900	750	500	115	200	70	85	45
150	6	307	307	950	950	500	-	-	-	1175	965	500	145	245	105	130	60
200	8	350	315	1085	1115	350	1225	800	225	1255	1075	500	175	420	150	200	110
250	10	385	407	1270	1305	400	1515	1050	300	1635	1500	500	210	495	200	270	140
300	12	395	532	1470	1500	500	1615	1185	305	1735	1700	500	240	600	250	330	200
350	14	385	672	1720	1760	600	1880	1345	455	2025	1917	500	285	640	310	400	270
400	16	420	820	1970	1975	650	2025	1475	455	2160	1920	500	330	720	350	450	300
450	18	455	980	2185	1985	700	2175	1615	455	2300	1985	500	375	795	410	540	360
500	20	457	715	2525	1935	800	2365	1715	455	2445	1715	500	385	875	410	540	370
600	24	520	810	2875	1985	900	2645	2125	455	2795	2195	457	435	1050	410	540	430
700	28	585	915	-	-	-	-	-	-	3035	2475	457	485	1250	320	380	580
800	32	645	965	-	-	-	-	-	-	4125	2800	450	535	1375	450	450	670
900	36	715	1015	-	-	-	-	-	-	4805	3200	450	585	1500	500	500	780
1000**	40	871	-	-	-	-	-	-	-	5145	3645	450	635	1675	530	630	900

注：代号为100为CLASS 150的规格系列。

**CLASS 150的管道阀门适用规格。

***电动驱动为双向控制，可根据客户要求定制。

****重量单位为千克，1000.00为近似重量。

不包括附件重量。

Note: **Size 100 is only the structure length for CLASS 150

***No such specifications for pipeline valve of CLASS 150

****EAS EPICARD electric device, with order to user's request.

*****The weight listed is that of bare stem, FROD, no-dimension for

and not including drive unit.