

五方盲板Pressure: PN16-18 & CLASS 150-300



Fig.2094



Fig.2095




Fig.2096

主要尺寸及重量 Main dimensions & Weight

PN16, 18 CLASS 150

规格 Size		L1 mm	L2 mm	开阀时 Gate opened			全开时 Gate opened			全开时 Gate opened			重量 Weight kg	净重 Net Weight kg
mm	In.			M	M1	M2	H	H1	H2	H	H1	H2		
50	2	170	190	670	400	300	-	-	-	120	120	120	25	25
65	2-1/2	200	220	700	400	300	-	-	-	120	120	120	30	30
80	3	220	240	750	400	300	-	-	-	120	120	120	35	35
100	4	250	270	800	400	300	-	-	-	120	120	120	45	45
125	5	280	300	850	400	300	120	120	120	120	120	120	55	55
150	6	310	330	900	400	300	120	120	120	120	120	120	65	65
200	8	370	390	1000	400	300	120	120	120	120	120	120	85	85
250	10	430	450	1100	400	300	120	120	120	120	120	120	110	110
300	12	490	510	1200	400	300	120	120	120	120	120	120	135	135
350	14	550	570	1300	400	300	120	120	120	120	120	120	160	160
400	16	610	630	1400	400	300	120	120	120	120	120	120	185	185
450	18	670	690	1500	400	300	120	120	120	120	120	120	210	210
500	20	730	750	1600	400	300	120	120	120	120	120	120	235	235
550	22	790	810	1700	400	300	120	120	120	120	120	120	260	260
600	24	850	870	1800	400	300	120	120	120	120	120	120	285	285
650	26	910	930	1900	400	300	120	120	120	120	120	120	310	310
700	28	970	990	2000	400	300	120	120	120	120	120	120	335	335
750	30	1030	1050	2100	400	300	120	120	120	120	120	120	360	360
800	32	1090	1110	2200	400	300	120	120	120	120	120	120	385	385
850	34	1150	1170	2300	400	300	120	120	120	120	120	120	410	410
900	36	1210	1230	2400	400	300	120	120	120	120	120	120	435	435

PN16 CLASS 300

规格 Size		L1 mm	L2 mm	开阀时 Gate opened			全开时 Gate opened			全开时 Gate opened			重量** Weight kg	净重 Net Weight kg
mm	In.			M	M1	M2	H	H1	H2	H	H1	H2		
50	2	170	190	670	400	300	-	-	-	120	120	120	25	25
65	2-1/2	200	220	700	400	300	-	-	-	120	120	120	30	30
80	3	220	240	750	400	300	-	-	-	120	120	120	35	35
100	4	250	270	800	400	300	-	-	-	120	120	120	45	45
125	5	280	300	850	400	300	120	120	120	120	120	120	55	55
150	6	310	330	900	400	300	120	120	120	120	120	120	65	65
200	8	370	390	1000	400	300	120	120	120	120	120	120	85	85
250	10	430	450	1100	400	300	120	120	120	120	120	120	110	110
300	12	490	510	1200	400	300	120	120	120	120	120	120	135	135
350	14	550	570	1300	400	300	120	120	120	120	120	120	160	160
400	16	610	630	1400	400	300	120	120	120	120	120	120	185	185
450	18	670	690	1500	400	300	120	120	120	120	120	120	210	210
500	20	730	750	1600	400	300	120	120	120	120	120	120	235	235
550	22	790	810	1700	400	300	120	120	120	120	120	120	260	260
600	24	850	870	1800	400	300	120	120	120	120	120	120	285	285
650	26	910	930	1900	400	300	120	120	120	120	120	120	310	310
700	28	970	990	2000	400	300	120	120	120	120	120	120	335	335
750	30	1030	1050	2100	400	300	120	120	120	120	120	120	360	360
800	32	1090	1110	2200	400	300	120	120	120	120	120	120	385	385
850	34	1150	1170	2300	400	300	120	120	120	120	120	120	410	410
900	36	1210	1230	2400	400	300	120	120	120	120	120	120	435	435

注：*电动装置为分二道电源，*带报警信号装置。

**表中所示重量为尺寸，不包括驱动装置。

Note: **TwoVTON electric device, with models to user's requests.

**The weight listed is that of purchased, not including drive unit.