


**Fig. 04/1**

**齿轮传动  
Gear Operator**
**压力等级 Pressure CLASS400-1500**

- ◆ 压力等级范围
- ◆ class100.12 以上用厚球密封结构
- ◆ class100.12 以上用双球密封结构
- ◆ class1500 以上用厚球密封结构
  
- ◆ Pressure-rated inner
- ◆ class100.12 and above
- ◆ class100.12 and above
- ◆ class1500.12 and above gear operated

**主要尺寸及重量 Main dimensions & Weight**

压力等级 CLASS	口径 Size		尺寸 Dimensions						重量 Weight		重量单位 Unit	Cv值
	mm	in.	Lmm	Lin	Lmm	H	H <sub>1</sub>	H <sub>2</sub>	kg	lb		
100	80	3	338	334	388	508	-	380	80	-	175	100
	100	4	432	398	438	608	-	480	128	-	332	180
	150	6	528	462	532	695	-	570	225	-	618	440
	200	8	680	584	683	880	-	670	480	-	1208	760
	250	10	787	711	781	1158	-	810	780	-	2000	1400
150	80	3	381	328	384	428	-	380	108	-	-	100
	100	4	457	398	460	718	-	500	120	-	-	160
	150	6	618	528	613	1008	-	600	220	-	-	480
	200	8	727	688	730	1358	-	680	320	-	-	800
	250	10	838	797	841	-	1518	810	1000	-	1440	1200
200	80	3	478	478	473	638	-	6380	-	98	-	98
	100	4	548	548	548	778	-	680	-	138	-	138
	150	6	780	780	771	1080	-	670	-	400	-	380
	200	8	832	832	841	-	1480	680	-	680	-	680
	250	10	991	991	1000	-	1540	880	-	1200	840	1000